DRY FUEL

Product ID: 80008

Product description

Dry Fuel (water remover) is developed to absorb and remove (condensation) water from both petrol and diesel fuel tanks. Prevents fuel system corrosion and stops or reduces white smoke.

Benefits

- ✓ Absorbs and removes water from both petrol and diesel fuel tanks
- ✓ Stops or reduces white smoke emission
- ✓ Protects against rust and corrosion
- ✓ Prevents fuel filter (and carburettor) icing
- ✓ Provides a better cold start performance
- ✓ Prevents bacterial growth

Usage

Recommended for all petrol and diesel engines with or without turbocharger. Will not harm catalytic converters.

Direction

Pour the contents of one bottle in the fuel tank before filling it to the maximum level.

Dosage

One bottle treats 40-60 litres of fuel.
For best results, use every six months.

Technical specification

Density g/cm³:	0,810
Flash point:	22°C
Colour:	Light blue / transparent
Odour:	Characteristic

The information in this sheet is correct and true to the best of our knowledge, but any recommendations or suggestions made in this sheet are made without guarantee since the conditions of use are beyond our control. We do not accept responsibility for damage as a consequence of incompleteness, negligence and/or inaccuracies in this information sheet. The above typical values do not constitute a specification nor does the information in this sheet imply any legally binding assurance of certain properties or of suitability for a specific purpose. All Terms of Sale of Technical Lubricants International B.V. are applied here. **Updated 06/2021**