



# HEATING OIL ADDITIVE

Product ID: 80067

## Product description

State-of-the-art multipurpose additive to increase the quality and storability of heating oil. Contains additives to reduce corrosion and oxidation and to stabilize the fuel quality. A special re-odorant helps to cover the typical smell of heating oil. Can also be used as a fuel stabilizer in agricultural diesel fuel.

## Benefits

- ✓ Improves performance due to a more complete combustion;
- ✓ Cleans filters, nozzles and other parts of the fuel system;
- ✓ Improves (storage) stability: protects against ageing of the fuel;
- ✓ Contains a metal deactivator to reduce oxidation;
- ✓ Corrosion inhibitors reduce corrosion of the entire fuel system;
- ✓ Limits build-up of sludge and sediments and lubricates the fuel pump, reducing risk of system failure;
- ✓ Lowers heating, maintenance and operating costs;
- ✓ Provides an ashless combustion
- ✓ Pleasant fragrance to cover the typical smell of heating oil.

## Usage

All heating oil burner technologies.

## Direction

Pour the contents of one bottle in the tank before filling it with fuel.

## Dosage

1L treats 2000L of heating oil

## Technical specification

Density g/cm <sup>3</sup> :	0,9 at 15°C
Flash Point:	> 61°C
Colour:	slightly yellow
Odour:	fruity/sweet

The information in this sheet is correct and true to the best of our knowledge, but any recommendations or suggestions made in this sheet are made without guarantee since the conditions of use are beyond our control. We do not accept responsibility for damage as a consequence of incompleteness, negligence and/or inaccuracies in this information sheet. The above typical values do not constitute a specification nor does the information in this sheet imply any legally binding assurance of certain properties or of suitability for a specific purpose. All Terms of Sale of Technical Lubricants International B.V. are applied here. **Updated 06/2021**