



CHAIN SPRAY PREMIUM

Product ID: 80126



Product description

This chain spray combines the excellent lubricating characteristics of Boron Nitride and PTFE with the protective properties of a wax-based lubricant.

It has excellent penetration capabilities, is resistant to fresh and salt water and protects the surface against corrosion. Furthermore the synthetic ceramic additives in this grease provide the best lubrication at extreme temperatures and pressure. It is therefore a high-grade lubricant that provides 1st class chain protection from abrasion and corrosion.

Benefits

- ✓ Contains Boron Nitride and PTFE
- ✓ Reduces wear and friction
- ✓ Excellent thermal conductivity
- ✓ Extra additives to protect against corrosion
- ✓ Strong metal adhesion
- ✓ High penetrating power
- ✓ Water resistant, also from salt water
- ✓ Suitable for O-ring chains
- ✓ Resistant to high pressure
- ✓ Visible white lubricating film

Usage

Apply to protect or lubricate on all motorcycle and MTB parts subjected to high pressures, impacts and vibrations such as – but not limited to – (motorcycle)chains, gears, drive chains and cables. Also suitable for other applications where a corrosion protective wax-based grease with above properties is required.

Safety

Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Pressurized container: Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Avoid breathing spray. Wear protective gloves / eye protection. Use only outdoors or in a well ventilated area.

Direction/Dosage

Aerosol with propane/butane propellant. Shake well before use.

After application, wait for several minutes until the solvents are evaporated. Then wipe off excessive lubricant. To be used whenever required.

Technical specification

Density at 20°C:	0,65 g/cm ³
Propellant:	Propane, Butane
Flash Point:	-97°C
Ignition Point:	> 200°C
Colour:	Creamy white
Odour:	Characteristic

The information in this sheet is correct and true to the best of our knowledge, but any recommendations or suggestions made in this sheet are made without guarantee since the conditions of use are beyond our control. We do not accept responsibility for damage as a consequence of incompleteness, negligence and/or inaccuracies in this information sheet. The above typical values do not constitute a specification nor does the information in this sheet imply any legally binding assurance of certain properties or of suitability for a specific purpose. All Terms of Sale of Technical Lubricants International B.V. are applied here. **Updated 06/2021**