

A/C LEAK DETECTION DYE

Product ID: 80234



Product description

High quality leak detection dye to identify oil leaks in the air conditioning system of passenger cars, heavy duty vehicles, farm equipment and air tools. It is easy to use and mixes with existing oil.

Benefits

- ✓ Easy to use
- ✓ Identifies A/C oil system leaks
- ✓ Easily mixes with existing oil

Direction

1. Add the dye to directly into the oil reservoir
2. Once properly mixed the leak in the system can be identified by shining a UV light

Treat rate

Automotive AC	ACR 1kg	ACR 1-3kg	ACR- 3-6kg
7,5ml	7,5ml	15ml	30ml

Gases

- R-22
- R-134a
- R-1234yf
- Propane
- CO2

Technical specification

Viscosity @ 40°C (cSt):	38
Viscosity @ 100°C (cSt):	5,5
Viscosity Index (VI):	69
Flash Point (°C) (cSt):	210

The information in this sheet is correct and true to the best of our knowledge, but any recommendations or suggestions made in this sheet are made without guarantee since the conditions of use are beyond our control. We do not accept responsibility for damage as a consequence of incompleteness, negligence and/or inaccuracies in this information sheet. The above typical values do not constitute a specification nor does the information in this sheet imply any legally binding assurance of certain properties or of suitability for a specific purpose. All Terms of Sale of Technical Lubricants International B.V. are applied here. **Updated 06/2021**