



ADHESIVE CLEAR GREASE (CHAIN LUBE)

Product ID: 80501

Product description

Adhesive Clear Grease (Chain lube) is a high-grade synthetic and extremely versatile lubricant. ACL 2000 is an excellent adhesive yet penetrating and high-pressure resistant lubricant. ACL 2000 shows extreme penetrating and moisture displacing properties while creating a strong and lasting adhesive lubricant film on all moving and rotating parts to minimize wear, friction and corrosion. ACL 2000 is especially designed for lubricating parts subject to high pressure, speed, impact and vibration, however is also very suited as a universal lubricant for applications where a strong, lasting and protective lubricant film is required. Operating temperature range: from -35°C to 200°C. Contains no silicone, resin or acid.

Benefits

- ✓ Excellent penetrating properties
- ✓ Effective adhesiveness
- ✓ Extraordinarily tear-resistant lubricating film
- ✓ Protects against corrosion
- ✓ Excellent protection against wear
- ✓ Resistant to high temperatures and high pressure
- ✓ Does not affect rubber, plastics or paint
- ✓ Resistant to water, salt, alkalines and weak acids

Usage

Universally applicable for a wide range of applications where a strong and durable lubricant film is required, like for example chains, hinges, shift, clutch and throttle linkages, Bowden cables and a very wide range of other applications.

Direction

Spraying distance: 10-15 cm. Spray the product sufficiently on the parts to be treated. A few minutes after application the solvent evaporates leaving a highly adhesive, waterproof load bearing lubricant.

Dosage

To be used whenever required.

Technical specification

Operating temperature:	-35°C to 200°C
Colour:	Transparent / Yellowish
Odour:	Characteristic
Solvent:	Hydrocarbon

The information in this sheet is correct and true to the best of our knowledge, but any recommendations or suggestions made in this sheet are made without guarantee since the conditions of use are beyond our control. We do not accept responsibility for damage as a consequence of incompleteness, negligence and/or inaccuracies in this information sheet. The above typical values do not constitute a specification nor does the information in this sheet imply any legally binding assurance of certain properties or of suitability for a specific purpose. All Terms of Sale of Technical Lubricants International B.V. are applied here. **Updated 06/2021**