



MOTOR OIL TREATMENT + MOS2



Product ID: 80033

Product description

TecLub Motor Oil Treatment + MoS2 is a dispersion of Molybdenum Sulphide in a highly refined petroleum oil. Due to the exclusive particle selection as well as a highly sophisticated production process, it has a remarkably high stability compared to similar products.

Benefits

- ✓ Reduces friction and wear by forming an adhesive MoS2 film on all moving surfaces inside the engine
- ✓ Reduces fuel and oil consumption and lowers toxic emissions
- ✓ Restores engine power
- ✓ The lubricating MoS2 film guarantees lubrication during cold starts and in case of emergencies
- ✓ Provides effective long term protection of your engine and ensures optimal performance

Usage

For all gasoline, diesel and LPG engines with or without turbochargers. Can be mixed with all commercially available engine oils. Does not clog filters and is not harmful for catalytic converters. Not suitable for motorcycles with a wet clutch.

Direction

Add contents of one bottle to the warm motor oil. Make sure the oil contents do not exceed the maximum oil level in your engine.

Dosage

One bottle treats 4 to 6 litres of motor oil.

Technical specification

Density g/cm ³ :	0,87
Flash point:	> 220°C
Colour:	Black
Brookfield viscosity:	300 cP
(SP01, 100 RPM@ 25°C)	

The information in this sheet is correct and true to the best of our knowledge, but any recommendations or suggestions made in this sheet are made without guarantee since the conditions of use are beyond our control. We do not accept responsibility for damage as a consequence of incompleteness, negligence and/or inaccuracies in this information sheet. The above typical values do not constitute a specification nor does the information in this sheet imply any legally binding assurance of certain properties or of suitability for a specific purpose. All Terms of Sale of Technical Lubricants International B.V. are applied here.

Updated 06/2021