



# FUEL STABILIZER



Product ID: 80006

## Product description

Fuel Stabilizer is a highly effective fuel additive developed to protect, preserve and stabilize petrol and diesel fuel during prolonged periods of (winter) storage.

## Benefits

- ✓ Protects and stabilizes fuel over a prolonged period of storage
- ✓ Controls gum, varnish and colour insolubles
- ✓ Provides corrosion protection
- ✓ Controls darkening and oxidation of fuel
- ✓ Prevents rust and keeps fuel system clean
- ✓ Eliminates need to drain fuel prior to storage
- ✓ Ensures quick, easy starts after storage

## Usage

For use in all 2-stroke and 4-stroke petrol, diesel and LPG engines with or without turbochargers.

## Direction

Shake briefly. Pour the required contents of a bottle in the petrol or diesel fuel tank. Operate engine for about ten minutes to ensure the treated fuel reaches all parts of the fuel system.

## Dosage

Single shot formulation: one bottle treats 50 litres of fuel.

Dosing bottle formulation: 50 ml treats 50 litres of fuel.

## Technical specification

Density g/cm <sup>3</sup> :	0,790 – 0,830
Flash point:	> 61°C
Colour:	Amber (clear)
Odour:	Characteristic

The information in this sheet is correct and true to the best of our knowledge, but any recommendations or suggestions made in this sheet are made without guarantee since the conditions of use are beyond our control. We do not accept responsibility for damage as a consequence of incompleteness, negligence and/or inaccuracies in this information sheet. The above typical values do not constitute a specification nor does the information in this sheet imply any legally binding assurance of certain properties or of suitability for a specific purpose. All Terms of Sale of Technical Lubricants International B.V. are applied here. Updated 09/2023 - V4