



# INJECTION SYSTEM PURGE FOR PETROL



Product ID: 80013

## Product description

Injection System Purge for Petrol is a very concentrated and effective direct cleaner for the entire petrol fuel system. Thoroughly cleans injectors, inlet valves and ports and the combustion chamber without the need for disassembly. To be used with a compatible fuel (injector) cleaning device.

## Benefits

- ✓ Cleans injectors, valves, valve stems, piston, piston rings and the combustion chamber without the need for disassembly.
- ✓ Restores injection spray pattern and injection time.
- ✓ Frees and prevents sticking exhaust valves.
- ✓ Eliminates rough idling, engine hesitation and improves starting.
- ✓ Reduces petrol consumption.
- ✓ Restores power and performance and optimizes engine operation.
- ✓ Reduces emission of hazardous exhaust gases.

## Usage

All petrol (leaded or unleaded) engines with direct or indirect injection systems. Will not harm catalytic converters.

## Direction

- ✓ For professional use only.
- ✓ Product is ready-to-use and does not need to be mixed with petrol.
- ✓ Use maximum one bottle (1L) for full and optimized cleaning.
- ✓ To be used only with professional equipment suitable for direct fuel supply to the engine.
- ✓ Follow the instructions of the equipment supplier for application and connection to the car's engine.
- ✓ Make sure the engine is at normal operating temperature when applying this product.
- ✓ DO NOT ADD TO THE FUEL TANK.
- ✓ For best results drive the vehicle for 10 to 20 minutes at elevated RPM directly after treatment.

## Dosage

Recommended treatment every 25.000 km or when problems like poor running or starting, rough idling or excessive exhaust emissions occur.

For a complete treatment and rejuvenation of the engine we recommend that an air intake cleaning service is done with TecLub Intake & Combustion Chamber Cleaner followed by flushing the engine oil system with TecLub Engine Flush. Afterwards drain the engine oil and refill with fresh recommended engine oil and replace the engine oil filter with a new one.

## Technical specification

Density g/cm <sup>3</sup> :	0,776
Flash point:	< 0°C
Colour:	Clear / Amber
Odour:	Characteristic

The information in this sheet is correct and true to the best of our knowledge, but any recommendations or suggestions made in this sheet are made without guarantee since the conditions of use are beyond our control. We do not accept responsibility for damage as a consequence of incompleteness, negligence and/or inaccuracies in this information sheet. The above typical values do not constitute a specification nor does the information in this sheet imply any legally binding assurance of certain properties or of suitability for a specific purpose. All Terms of Sale of Technical Lubricants International B.V. are applied here.

**Updated 06/2021 V3**